

SPEC SHEET ABT-HC-12S-TS

Product Name:	ABT-HC-12S-TS
Features:	<ul style="list-style-type: none"> • TempLog Premier Solid Door Laboratory Refrigerator • 12 Cu. Ft. capacity • One swing solid door, self-closing, right hinged, not reversible • Microprocessor temperature controller • Adjustable operating temperature range: 1°C - 10°C • Touch Screen Digital Temperature Display and Alarm Module with battery backup to support temperature monitoring and alarms • Password-protected control panel • Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit • Active temperature scale bar display, Digital 24-hour temperature chart, Temperature data logging • Resettable 1-point min/max history • USB port for data transfer and software updates • Real-time operational display clock • 4-20mA output • Electronic troubleshooting guide, Electronic QR Code to access Owner's Manual & technical support contact information • Adjustable alarm volume • Audible and visual high/low temperature alarms • 2 probes; 1 in air and 1 in sample bottle • Sensor error alarm, Power failure alarm, Door ajar alarm, Low battery alarm • Operation indicator • Alarm validation (audible, visual, and remote alarm) • Alarm mute with ring back, Remote alarm contacts • Three adjustable shelves (adjustable in ½" increments) • Forced draft air circulation • Keyed door lock, Heavy duty door handle, Magnetic door gasket for positive seal • LED interior lights are safety shielded and switch controlled • Swivel casters (3 ½"), Probe access port (3/8") • White powder-coated steel exterior and interior • Hydrocarbon, natural refrigerant (R290) • Three year parts and labor warranty, plus an additional two year compressor parts warranty • Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters • Cycle defrost • 115V, 60 Hz, 3 Amps, 1/5 HP • ETL listed • Shipping weight: 227 lbs.