

**SPEC SHEET**    **ABT-HC-CS-23**

<b>Product Name:</b>	ABT-HC-CS-23
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Standard Glass Door Chromatography Refrigerator</li> <li>• 23 Cu. Ft. capacity</li> <li>• One swing glass door, self-closing, right hinged, not reversible</li> <li>• Microprocessor temperature controller</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Remote alarm contacts</li> <li>• Adjustable operating temperature range: 1°C – 10°C</li> <li>• Keyed door lock</li> <li>• One GFCI protected duplex electrical outlet</li> <li>• One 2" access port with spring-loaded, self-closing gasketed metal cover</li> <li>• Magnetic door gasket for positive seal</li> <li>• Heavy duty door handle</li> <li>• Four adjustable shelves (adjustable in 1/2" increments)</li> <li>• Forced draft air circulation</li> <li>• LED interior lights are safety shielded and switch controlled</li> <li>• Swivel Casters (3 1/2")</li> <li>• Probe access port (3/8")</li> <li>• Advanced hydrocarbon detector</li> <li>• White powder-coated steel exterior and interior</li> <li>• High density urethane foam cabinet insulation</li> <li>• Hydrocarbon, natural refrigerant (R290)</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts warranty</li> </ul>

**SPEC SHEET**    **ABT-HC-CS-23**

<b>Product Name:</b>	ABT-HC-CS-23
<b>Features:</b>	<ul style="list-style-type: none"><li>• Exterior dimensions: 27 5/8" W x 34 3/4" D x 81 3/4" H with casters; 78 1/4" H without casters</li><li>• Cycle defrost</li><li>• 115V, 60 Hz, 3 Amps, 1/5 HP</li><li>• ETL listed</li><li>• Shipping weight: 336 lbs.</li><li>• Note: This unit requires two (2) outlets</li></ul>