

**SPEC SHEET ABT-HC-EFP-17**

<b>Product Name:</b>	ABT-HC-EFP-17
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Standard Hazardous Location (Explosion Proof) Freezer</li> <li>• 17 Cu. Ft. Capacity</li> <li>• One solid swing door, right hinged, not reversible</li> <li>• Microprocessor Temperature Controller</li> <li>• Adjustable operating temperature range: -15°C – -25°C</li> <li>• Six fixed shelves</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> <li>• Heavy duty door handle</li> <li>• Leveling legs</li> <li>• White textured cabinet and door</li> <li>• High density urethane foam cabinet and door insulation</li> <li>• Hydrocarbon, natural refrigerant (R290)</li> <li>• Exterior dimensions: 30 3/4"W x 28 5/8"D x 67 3/4"H</li> <li>• Manual defrost</li> <li>• Not equipped with line cord and plug; must be hardwired in conduit to 120 VAC power source</li> <li>• 115V, 60Hz, 6 Amps, 1/2 HP</li> <li>• ETL listed</li> <li>• Two year parts and labor warranty</li> <li>• Meet NFPA and OSHA guidelines for hazardous locations, Class 1, Division II, Group C &amp; D. These units are engineered for use in environments where volatile / explosive conditions could potentially exist. For storage of flammable or volatile materials within typical laboratory or non-volatile environments, see Flammable Material Storage units</li> <li>• Shipping weight: 220 lbs.</li> </ul>