

**SPEC SHEET**    **ABT-HC-LS-12**

<b>Product Name:</b>	ABT-HC-LS-12
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Standard Glass Door Laboratory Refrigerator</li> <li>• 12 Cu. Ft. Capacity</li> <li>• One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged</li> <li>• Microprocessor temperature controller</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Remote alarm contacts</li> <li>• Adjustable operating temperature: 1°C to 10°C</li> <li>• Three adjustable shelves (adjustable in ½" increments)</li> <li>• Forced draft air circulation</li> <li>• Keyed door lock and Magnetic door gasket for positive seal</li> <li>• Heavy duty door handle</li> <li>• Swivel casters (3 ½"); Probe access port (3/8")</li> <li>• LED interior lights are safety shielded and switch controlled</li> <li>• Powder coated steel white interior and exterior</li> <li>• High density urethane foam cabinet insulation</li> <li>• Hydrocarbon, natural refrigerant (R290)</li> <li>• One year parts and labor warranty, plus an additional four year compressor parts warranty</li> <li>• Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters</li> <li>• Cycle defrost</li> <li>• 115V, 60 Hz, 3 Amps, 1/5 HP</li> <li>• ETL listed</li> <li>• Shipping weight: 258 lbs.</li> </ul>