

SPEC SHEET ABT-HC-LS-72

Product Name:	ABT-HC-LS-72
Features:	<ul style="list-style-type: none"> • Standard Glass Door Laboratory Refrigerator • 72 Cu. Ft. Capacity • Three swing glass doors, self-closing (energy efficient, double pane vacuum insulated) • Microprocessor temperature controller and Digital temperature display • Audible and visual high and low temperature alarms • 2 probes; 1 in air and 1 in sample bottle • Remote alarm contacts • Adjustable operating temperature: 1°C to 10°C • Twelve adjustable shelves (adjustable in ½" increments) • Forced draft air circulation • Keyed door lock • Magnetic door gasket for positive seal • Heavy duty door handles • Swivel casters (3 ½"); Probe access port (3/8") • LED interior lights are safety shielded and switch controlled • Powder coated steel white interior and exterior • High density urethane foam cabinet insulation • Hydrocarbon, natural refrigerant (R290) • One year parts and labor warranty, plus an additional four year compressor parts warranty • Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters • Cycle defrost • 115V, 60 Hz, 7.5 Amps, 1/2 HP • ETL listed • Shipping weight: 743 lbs.