

**SPEC SHEET**    **ABT-HC-UCFS-0504**

<b>Product Name:</b>	ABT-HC-UCFS-0504
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Premier Undercounter Refrigerator Freestanding</li> <li>• 5.2 Cu. Ft. Capacity</li> <li>• One solid swing door, right hinged, not reversible</li> <li>• Microprocessor temperature controller</li> <li>• Adjustable operating temperature range: 1°C – 10°C</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• Remote alarm contacts</li> <li>• 2 probes; 1 in air and 1 in glycol bottle</li> <li>• Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall</li> <li>• Bottom footed shelf to allow air circulation</li> <li>• Back wall evaporator cover</li> <li>• Forced draft circulation</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> <li>• Leveling legs</li> <li>• LED interior light</li> <li>• Switch activated light</li> <li>• Probe access port (3/8")</li> <li>• Powder coat exterior</li> <li>• High density urethane foam cabinet insulation</li> <li>• HFC-free refrigerant (R600a), foam insulation and packaging</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts only warranty</li> <li>• Pyxis®, Omnicell® and AcuDose RX® compatible</li> <li>• Exterior dimensions: 23 3/4" W x 24" D x 32 1/8" H</li> </ul>

**SPEC SHEET**    **ABT-HC-UCFS-0504**

<b>Product Name:</b>	ABT-HC-UCFS-0504
<b>Features:</b>	<ul style="list-style-type: none"><li>• Note: This unit must have 4" clearance on sides and back for adequate ventilation</li><li>• Cycle defrost</li><li>• 115V, 60 Hz, 1.3 Amps, 1/6 HP</li><li>• UL/C-UL listed</li><li>• Shipping weight: 129 lbs.</li></ul>