

**SPEC SHEET CRT-ABT-HC-S16G**

<b>Product Name:</b>	CRT-ABT-HC-S16G
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Upright Controlled Room Temperature Cabinet, Glass Door</li> <li>• 16 Cu. Ft. Capacity</li> <li>• One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible</li> <li>• Microprocessor temperature controller</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• Remote alarm contacts</li> <li>• Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</li> <li>• Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Three adjustable shelves</li> <li>• Vaccine storage power cord warning label</li> <li>• Forced draft air circulation</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> <li>• Heavy duty door handle</li> <li>• Swivel Casters (3”)</li> <li>• LED interior lights are safety shielded and switch controlled</li> <li>• Probe access port (3/8”)</li> <li>• Powder coated steel white interior and exterior</li> <li>• High density urethane foam cabinet insulation</li> <li>• Hydrocarbon, natural refrigerant (R290)</li> </ul>

**SPEC SHEET** CRT-ABT-HC-S16G

<b>Product Name:</b>	CRT-ABT-HC-S16G
<b>Features:</b>	<ul style="list-style-type: none"><li>• One year parts and labor warranty, plus an additional four year compressor parts warranty</li><li>• Exterior dimensions: 25" W x 29 ¾" D x 79" H with casters; 75 ½" H without casters</li><li>• Cycle defrost</li><li>• 115V, 60 Hz, 3 Amps, 1/5 HP</li><li>• UL/C-UL listed</li><li>• Shipping weight: 275 lbs.</li></ul>