

SPEC SHEET CRT-ABT-HC-S16S

Product Name:	CRT-ABT-HC-S16S
Features:	<ul style="list-style-type: none"> • Upright Controlled Room Temperature Cabinet , Solid Door • 16 Cu. Ft. capacity • One swing solid door, self-closing, right hinged, not reversible • Microprocessor temperature controller • Digital temperature display • Audible and visual high and low temperature alarms • Remote alarm contacts • Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • 2 probes; 1 in air and 1 in sample bottle • Three adjustable shelves • Vaccine storage power cord warning label • Forced draft air circulation • Heavy duty door handle • Keyed door lock • Magnetic door gasket for positive seal • LED interior lights are safety shielded and switch controlled • Swivel Casters (3”) • Probe access port (3/8”) • White powder-coated steel exterior and interior • Hydrocarbon, natural refrigerant (R290) • One year parts and labor warranty, plus an additional four year compressor parts warranty

SPEC SHEET CRT-ABT-HC-S16S

Product Name:	CRT-ABT-HC-S16S
Features:	<ul style="list-style-type: none">• Exterior dimensions: 25" W x 29 ¾" D x 79" H with casters; 75 ½" H without casters• Cycle defrost• 115V, 60 Hz, 3 Amps, 1/5 HP• ETL listed• Shipping weight: 277 lbs.