

# SPEC OF AT200P-9

STP-JX-Tip-AT200P-9-A1

GEB Robotic Tips for PerkinElmer Janus® can be used for high-throughput pipetting processes in proteomics, drug development, genomics and other fields.

## Product details at-a-glance

GEB Cat#	Max Volume	Tip Color	Low Retention	Sterilized	Filtered (3.8*3.5)mm	Packaging Spec.
AT200P-9-N	200ul	Natural				96 tips/rack, 10 racks /pack, 5 packs / case.50 racks/case, 4800tips/case.
AT200P-9-N-LB	200ul	Natural	Low Retention			
AT200P-9-NS	200ul	Natural		Sterilized		
AT200P-9-NS-LB	200ul	Natural	Low Retention	Sterilized		
AF200PP-9-NS	200ul	Natural		Sterilized	Filtered	
AF200P-9-NS-LB	200ul	Natural	Low Retention	Sterilized	Filtered	
AT200P-9-X	200ul	Black				96 tips/rack, 10 racks /pack, 5 packs / case,50 racks/case, 4800tips/case. (Conductive black)
AT200P-9-X-LB	200ul	Black	Low Retention			
AT200P-9-XS	200ul	Black		Sterilized		
AT200P-9-XS-LB	200ul	Black	Low Retention	Sterilized		
AF200P-9-XS	200ul	Black		Sterilized	Filtered	
AF200P-9-XS-LB	200ul	Black	Low Retention	Sterilized	Filtered	
Case dimension L*W*H:500* 285*405mm			Gross Weight : 10.0kg			

- ✧ 200µL Liquid Level Sensing Tips
- ✧ 96 Tip/Hanging Tip Rack format
- ✧ Polypropylene
- ✧ Certified DNase/RNase free
- ✧ Nonpyrogenic
- ✧ Presterile/Nonsterile
- ✧ Filtered(Filtered With aerosol-resistant filters)/NonFiltered
- ✧ Endotoxin-Safe meets USP/FDA standards
- ✧ Comply With USP 3127 (Heavy Metal Contamination) standards
- ✧ Compatibility: PerkinElmer Janus®, MultiProbe liquid workstations.

Drawing: 200µl (No tolerance Diameter tolerance: ±0.05mm , Height tolerance: ±0.25mm)

