

**SPEC SHEET PH-ABT-HC-72S**

<b>Product Name:</b>	PH-ABT-HC-72S
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Premier Pharmacy/Vaccine Solid Door Refrigerator</li> <li>• 72 Cu. Ft. capacity</li> <li>• Three swing solid doors, self-closing, right hinged, not reversible</li> <li>• Microprocessor Temperature Controller</li> <li>• Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)</li> <li>• Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable</li> <li>• Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</li> <li>• Sample simulated digital temperature display; .1° Resolution</li> <li>• Adjustable temperature display in Celsius or Fahrenheit</li> <li>• Audible and visual high/low temperature alarms</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Sensor error alarm</li> <li>• Power failure alarm</li> <li>• Resettable 1-point Min/Max History</li> <li>• Remote alarm contacts</li> <li>• Alarm validation (audible, visual, and remote alarm)</li> <li>• Alarm mute with ring back</li> <li>• 18 total shelves, 12 adjustable plus 6 additional</li> <li>• Vaccine storage power cord warning label</li> <li>• Forced draft air circulation</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> </ul>

**SPEC SHEET PH-ABT-HC-72S**

<b>Product Name:</b>	PH-ABT-HC-72S
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Heavy duty door handle</li> <li>• LED interior lights are safety shielded and switch controlled</li> <li>• Swivel Casters (3 1/2")</li> <li>• Probe access port (3/8")</li> <li>• White powder-coated steel exterior and interior</li> <li>• Hydrocarbon, natural refrigerant (R290)</li> <li>• Pharmacy refrigerator/freezer toolkit and temperature logs</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts warranty</li> <li>• Exterior dimensions: 81" W x 34" D x 81 3/4" H with casters; 78 1/4" H without casters</li> <li>• Cycle defrost</li> <li>• 115V, 60 Hz, 7.5 Amps, 1/2 HP</li> <li>• ETL listed</li> <li>• Shipping weight: 600 lbs.</li> </ul>