



SPEC SHEET ABT-115V-2186

Features: • Ultra Low Temperature Freezer • 21 Cu.Ft. Capacity • One solid swing exterior door, right hinged, not reversible • Five insulated inner doors • Microprocessor controller specifications • Touch pad keys and four line display for easy programming • Large LED temperature readout • Audible and visual alarms with silence key for audible alarms • Programmable high and low temperature alarm set points • Programmable access code to limit access to set points and controller configuration • Automatic voltage boost to compensate for low line voltages • Normally open, normally closed alarm contacts and 4-20mA signal available to connect to central alarm system • RS-232 serial output • Battery backup on electronics during power outages • Temperature range: -50°C to -86°C • Four stainless steel shelves, adjustable on ½" centers • Cam action handle for one hand latching of exterior door. • Handle supplied with key lock and door switch for audible and visual alarms • Four heavy duty swivel casters with locks • Vacuum relief port for quick access after door closures • CFC-free refrigerant • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Exterior dimensions: 29.1"W x 23"D x 50"H
 2" box capacity: 400 ea. Upright freezer rack capacity: 25 ea. UF442 racks 115V, 60Hz, 16 amp, HP: ½ x ½ UL/C-UL listed NEMA plug configuration: NEMA 5-20 Cascade refrigeration system