



SPEC SHEET ABT-HC-10PS

Product Name:	ABT-HC-10PS
Features:	Premier Solid Door Compact Laboratory Refrigerator
	• 10.5 Cu. Ft. Capacity
	One solid swing door, right hinged, not reversible
	Microprocessor temperature controller
	Digital temperature display
	Audible and visual high and low temperature alarms
	• 2 probes; 1 in air and 1 in sample bottle
	Remote alarm contacts
	Adjustable operating temperature range: 1°C to 10°C
	• Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall
	Bottom footed shelf to allow air circulation
	Back wall evaporator cover
	Forced draft circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Leveling legs
	LED interior light
	Probe access port (3/8")
	Powder coat exterior
	High density urethane foam cabinet insulation
	HFC-free refrigerant (R600a), foam insulation and packaging
	• Two year parts and labor warranty, plus an additional three year compressor parts warranty
	• Exterior dimensions: 23 $\frac{3}{4}$ "W x 26 $\frac{1}{2}$ "D x 59"H
	 Note: This unit must have 4" clearance on sides and back for adequate ventilation
	UL/C-UL listed
	ENERGY STAR CERTIFIED
	Cycle defrost
	• 115V, 60 Hz, 1/3 HP, 2.3 Amps
	Energy Consumption 2.42 kWh/day
	Shipping weight: 183 lbs.