

SPEC SHEET ABT-HC-23

Product Name:	ABT-HC-23
Features:	<ul style="list-style-type: none"> • Premier Glass Door Laboratory Refrigerator • 23 Cu. Ft. capacity • One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged • Microprocessor Temperature Controller • Adjustable operating temperature range: 1°-10°C • Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms • Sample simulated digital temperature display; .1° Resolution • Adjustable temperature display in Celsius or Fahrenheit • Audible and visual high/low temperature alarms • Sensor error alarm, Power failure alarm • Resettable 1-point Min/Max History • Remote alarm contacts • Alarm validation (audible, visual, and remote alarm) • Alarm mute with ring back • Four adjustable shelves (adjustable in 1/2" increments) • Forced draft air circulation • Keyed door lock • Magnetic door gasket for positive seal • Recessed door handle • LED interior lights are safety shielded and switch controlled • Swivel casters (adds 4" to height), Probe access port (3/8") • White laminated vinyl exterior • White aluminum liner and stainless steel floor interior • HFC-free refrigerant (R290), foam insulation and packaging • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Exterior dimensions: 27" W x 30 1/2"D x 82 5/8" H with casters; 78 5/8" H without casters • Cycle defrost • 115V, 60 Hz, 5.4 Amps, 1/3 HP, BTU/HR 4932 • UL/C-UL listed • Shipping weight: 375 lbs.