

SPEC SHEET ABT-HC-26

Product Name:	ABT-HC-26
Features:	<ul style="list-style-type: none"> • Premier Glass Door Laboratory Refrigerator • 26 Cu. Ft. capacity • One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged • Microprocessor Temperature Controller • Adjustable operating temperature range: 1°-10°C • Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms • Sample simulated digital temperature display; .1° Resolution • Adjustable temperature display in Celsius or Fahrenheit • Audible and visual high/low temperature alarms • Sensor error alarm • Power failure alarm • Resettable 1-point Min/Max History • Remote alarm contacts • Alarm validation (audible, visual, and remote alarm) • Alarm mute with ring back • Four adjustable shelves (adjustable in 1/2" increments) • Forced draft air circulation • Keyed door lock • Magnetic door gasket for positive seal • Recessed door handle • LED interior lights are safety shielded and switch controlled • Swivel casters (adds 4" to height) • Probe access port (3/8")

SPEC SHEET ABT-HC-26

Product Name:	ABT-HC-26
Features:	<ul style="list-style-type: none"> • White laminated vinyl exterior • White aluminum liner and stainless steel floor interior • HFC-free refrigerant (R290), foam insulation and packaging • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Exterior dimensions: 30" W x 30 1/2" D x 82 5/8" H with casters; 78 5/8" H without casters. • Cycle defrost • 115V, 60 Hz, 5.4 Amps, 1/3 HP, BTU/HR 4932 • UL/C-UL listed • ENERGY STAR CERTIFIED • Shipping weight: 345 lbs.