

**SPEC SHEET ABT-HC-35**

<b>Product Name:</b>	ABT-HC-35
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Premier Glass Door Laboratory Refrigerator</li> <li>• 35 Cu. Ft. capacity</li> <li>• Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated)</li> <li>• Microprocessor Temperature Controller</li> <li>• Adjustable operating temperature range: 1°-10°C</li> <li>• Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</li> <li>• Sample simulated digital temperature display; .1° Resolution</li> <li>• Adjustable temperature display in Celsius or Fahrenheit</li> <li>• Audible and visual high/low temperature alarms</li> <li>• Sensor error alarm</li> <li>• Power failure alarm</li> <li>• Resettable 1-point Min/Max History</li> <li>• Remote alarm contacts</li> <li>• Alarm validation (audible, visual, and remote alarm)</li> <li>• Alarm mute with ring back</li> <li>• Eight adjustable shelves (adjustable in ½" increments)</li> <li>• Forced draft air circulation</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> <li>• Heavy duty door handles</li> </ul>

**SPEC SHEET ABT-HC-35**

<b>Product Name:</b>	ABT-HC-35
<b>Features:</b>	<ul style="list-style-type: none"> <li>• LED interior lights are safety shielded and switch controlled</li> <li>• Swivel casters (adds 4" to height)</li> <li>• Probe access port (3/8")</li> <li>• White laminated vinyl exterior</li> <li>• White aluminum liner and stainless steel floor interior</li> <li>• HFC-free refrigerant (R290), foam insulation and packaging</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts warranty</li> <li>• Exterior dimensions: 39 1/2" W x 31" D x 82 5/8" H with casters; 78 5/8" H without casters</li> <li>• Cycle defrost</li> <li>• 115V, 60 Hz, 6.2 Amps, 1/3 HP, BTU/HR 5265</li> <li>• UL/C-UL listed</li> <li>• Shipping weight: 407 lbs.</li> </ul>