



SPEC SHEET ABT-HC-72S-TS

Product Name:	ABT-HC-72S-TS
Features:	TempLog Premier Solid Door Laboratory Refrigerator
	• 72 Cu. Ft. capacity
	 Three swing solid doors, self-closing, right hinged, not reversible
	Microprocessor temperature controller
	Adjustable operating temperature range: 1°C - 10°C
	TempData-2000 Touch Screen Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms
	Password-protected control panel
	Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit
	Active temperature scale bar display
	Resettable 1-point min/max history
	Digital 24-hour temperature chart
	Temperature data logging
	USB port for data transfer and software updates
	Real-time operational display clock
	4-20mA output
	Electronic troubleshooting guide
	Electronic QR Code to access Owner's Manual & technical support contact information
	Adjustable alarm volume
	Audible and visual high/low temperature alarms
	2 probes; 1 in air and 1 in sample bottle
	Sensor error alarm
	Power failure alarm
	Door ajar alarm





SPEC SHEET ABT-HC-72S-TS

Product Name:	ABT-HC-72S-TS
Features:	 Low battery alarm Operation indicator Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Twelve adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door locks Magnetic door gasket for positive seal Heavy duty door handles LED interior lights are safety shielded and switch controlled Swivel casters (3 ½"), Probe access port (3/8") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) Three year parts and labor warranty, plus an additional two year compressor parts warranty Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters Cycle defrost 115V, 60 Hz, 7.5 Amps, 1/2 HP ETL listed Shipping weight: 600 lbs.