



## SPEC SHEET ABT-HC-CP-69

Product Name:	ABT-HC-CP-69
Product Name: Features:	ABT-HC-CP-69  Premier Glass Door Chromatography Refrigerator  69 Cu. Ft. capacity  Three sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm; Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Twelve adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  One GFCI protected duplex electrical outlet  Two 2" access ports with spring-loaded, self-closing gasketed metal covers  Magnetic door gasket for positive seal
	Two 2" access ports with spring-loaded, self-closing gasketed metal covers





## SPEC SHEET ABT-HC-CP-69

Product Name:	ABT-HC-CP-69
Features:	<ul> <li>Advanced hydrocarbon detector</li> <li>White powder-coated steel exterior and interior</li> <li>High density urethane foam cabinet insulation</li> <li>Hydrocarbon, natural refrigerant (R290)</li> <li>Two year parts and labor warranty, plus an additional three year compressor parts warranty</li> <li>Exterior dimensions: 82 1/2" W* x 33 1/4" D x 78 ¼" H without casters; 81 ¾" H with casters. *Width w/access ports closed; 90 1/2" width w/access ports open</li> <li>Cycle defrost</li> <li>115V, 60 Hz, 7.5 Amps, 1/2 HP</li> <li>ETL listed</li> <li>Shipping weight: 738 lbs.</li> <li>Note: This unit requires two (2) outlets</li> </ul>