



SPEC SHEET ABT-HC-CS-72

Product Name:	ABT-HC-CS-72
Features:	 Standard Glass Door Chromatography Refrigerator 72 Cu. Ft. capacity Three swing glass doors, self-closing, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: 1°C - 10°C Keyed door locks One GFCI protected duplex electrical outlet One 2" access port with spring-loaded, self-closing gasketed metal cover Heavy duty door handles Magnetic door gasket for positive seal Twelve adjustable shelves (adjustable in ½" increments) Forced draft air circulation LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½"), Probe access port (3/8") Advanced hydrocarbon detector White powder-coated steel exterior and interior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three year compressor parts warranty
	 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: 1°C - 10°C Keyed door locks One GFCI protected duplex electrical outlet One 2" access port with spring-loaded, self-closing gasketed metal cover Heavy duty door handles Magnetic door gasket for positive seal Twelve adjustable shelves (adjustable in ½" increments) Forced draft air circulation LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½"), Probe access port (3/8") Advanced hydrocarbon detector White powder-coated steel exterior and interior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three





SPEC SHEET ABT-HC-CS-72

Product Name:	ABT-HC-CS-72
Features:	 Exterior dimensions: 81 3/4" W x 34" D x 78 ¼" H without casters; 81 ¾" H with casters Cycle defrost 115V, 60 Hz, 7.5 Amps, 1/2 HP ETL listed Shipping weight: 743 lbs. Note: This unit requires two (2) outlets