



## SPEC SHEET ABT-HC-LP-16

Product Name:	ABT-HC-LP-16
Features:	<ul> <li>Premier Glass Door Laboratory Refrigerator</li> <li>16 Cu. Ft. capacity</li> <li>One swing glass door, self-closing, right hinged, not reversible</li> <li>Microprocessor Temperature Controller</li> <li>Adjustable operating temperature range: 1°-10°C</li> <li>Digital Temperature Display and Alarm Module</li> <li>Sample simulated digital temperature display; .1° Resolution</li> <li>Adjustable temperature display in Celsius or Fahrenheit</li> <li>Audible and visual high/low temperature alarms</li> <li>Sensor error alarm, Power failure alarm</li> <li>Resettable 1-point Min/Max History</li> <li>Remote alarm contacts</li> <li>2 probes; 1 in air and 1 in sample bottle</li> <li>Alarm mute with ring back</li> <li>Three adjustable shelves (adjustable in ½″ increments)</li> <li>Forced draft air circulation</li> <li>Keyed door lock</li> <li>Magnetic door gasket for positive seal</li> <li>Heavy duty door handle</li> <li>LED interior lights are safety shielded and switch controlled</li> <li>Swivel Casters (3 ½″), Probe access port (¾″)</li> <li>White powder-coated steel exterior and interior</li> <li>High density urethane foam cabinet insulation</li> <li>Hydrocarbon, natural refrigerant (R290)</li> </ul>





## SPEC SHEET ABT-HC-LP-16

Product Name:	ABT-HC-LP-16
Features:	<ul> <li>Two year parts and labor warranty, plus an additional three compressor parts warranty</li> <li>Exterior dimensions: 25" W x 29 3/4" D x 79" H with casters; 75 ½" H without casters</li> <li>Cycle defrost</li> <li>115V, 60 Hz, 3 Amps, 1/5 HP</li> <li>ETL listed</li> <li>Shipping weight: 283</li> </ul>