



## SPEC SHEET ABT-HC-LP-47-TS

| Product Name: | ABT-HC-LP-47-TS  |
|---------------|--|
| Features:     | Templog Premier Glass Door Laboratory Refrigerator   |
|               | • 47 Cu. Ft. capacity  |
|               | <ul> <li>Two sliding glass doors, self-closing (energy efficient, double<br/>pane vacuum insulated)</li> </ul>   |
|               | Microprocessor temperature controller  |
|               | <ul> <li>Adjustable operating temperature range: 1°C - 10°C</li> </ul>   |
|               | Touch Screen Digital Temperature Display and Alarm Module  |
|               | Password-protected control panel   |
|               | <ul> <li>Sample simulated digital temperature display; .1° Resolution,<br/>adjustable temperature display in Celsius or Fahrenheit</li> </ul>            |
|               | Active temperature scale bar display   |
|               | Resettable 1-point min/max history   |
|               | <ul> <li>Digital 24-hour temperature chart and Temperature data<br/>logging</li> </ul>   |
|               | <ul> <li>USB port for data transfer and software updates</li> </ul>  |
|               | Real-time operational display clock  |
|               | • 4-20mA output  |
|               | <ul> <li>Electronic troubleshooting guide and Electronic QR Code to<br/>access Owner's Manual &amp; technical support contact<br/>information</li> </ul> |
|               | Adjustable alarm volume  |
|               | <ul> <li>Audible and visual high/low temperature alarms</li> </ul>   |
|               | <ul> <li>2 probes; 1 in air and 1 in sample bottle</li> </ul>  |
|               | Sensor error alarm; Power failure alarm; Door ajar alarm   |
|               | Low battery alarm Operation indicator  |
|               | <ul> <li>Alarm validation (audible, visual, and remote alarm) and<br/>alarm mute with ring back</li> </ul>   |
|               | Remote alarm contacts  |
|               |  |





## SPEC SHEET ABT-HC-LP-47-TS

| Product Name: | ABT-HC-LP-47-TS   |
|---------------|---|
| Features:     | <ul> <li>Eight adjustable shelves (adjustable in ½" increments)</li> <li>Forced draft air circulation</li> <li>Keyed door locks</li> <li>Magnetic door gasket for positive seal</li> <li>Integrated door handles</li> <li>LED interior lights are safety shielded and switch controlled</li> <li>Swivel Casters (3 ½"); Probe access port (%")</li> <li>White powder-coated steel exterior and interior</li> <li>High density urethane foam cabinet insulation</li> <li>Hydrocarbon, natural refrigerant (R290)</li> <li>Three year parts and labor warranty, plus an additional two year compressor parts warranty</li> <li>Exterior dimensions: 54 1/8" W x 33 1/4" D x 81 ¾" H with casters; 78 ¼" H without casters</li> <li>Cycle defrost</li> <li>115V, 60 Hz, 4.5 Amps, 1/4 HP</li> <li>ETL listed</li> <li>Shipping weight: 508 lbs.</li> </ul> |