



## SPEC SHEET ABT-HC-LS-33

Product Name:	ABT-HC-LS-33
Features:	Standard Glass Door Laboratory Refrigerator
	• 33 Cu. Ft. Capacity
	<ul> <li>Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)</li> </ul>
	Microprocessor temperature controller
	Digital temperature display
	<ul> <li>Audible and visual high and low temperature alarms</li> </ul>
	<ul> <li>2 probes; 1 in air and 1 in sample bottle</li> </ul>
	Remote alarm contacts
	<ul> <li>Adjustable operating temperature: 1°C to 10°C</li> </ul>
	<ul> <li>Eight adjustable shelves (adjustable in <sup>1</sup>/<sub>2</sub>" increments)</li> </ul>
	Forced draft air circulation
	<ul> <li>Keyed door lock and Magnetic door gasket for positive seal</li> </ul>
	Integrated door handles
	<ul> <li>Swivel casters (3 <sup>1</sup>/<sub>2</sub>"); Probe access port (3/8")</li> </ul>
	<ul> <li>LED interior lights are safety shielded and switch controlled</li> </ul>
	<ul> <li>Powder coated steel white interior and exterior</li> </ul>
	<ul> <li>High density urethane foam cabinet insulation</li> </ul>
	<ul> <li>Hydrocarbon, natural refrigerant (R290)</li> </ul>
	<ul> <li>One year parts and labor warranty, plus an additional four year compressor parts warranty</li> </ul>
	<ul> <li>Exterior dimensions: 39 5/8" W x 33 ¼" D x 81 ¾" H with casters; 78 ¼" H without casters</li> </ul>
	Cycle defrost
	• 115V, 60 Hz, 4.5 Amps, 1/4 HP
	ETL listed
	Shipping weight: 419 lbs.