



## SPEC SHEET ABT-HC-LS-36

Product Name:	ABT-HC-LS-36
Features:	Standard Glass Door Laboratory Refrigerator
	• 36 Cu. Ft. Capacity
	<ul> <li>Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated)</li> </ul>
	Microprocessor temperature controller
	<ul> <li>Audible and visual high and low temperature alarms</li> </ul>
	2 probes; 1 in air and 1 in sample bottle
	Remote alarm contacts
	<ul> <li>Adjustable operating temperature: 1°C to 10°C</li> </ul>
	<ul> <li>Eight adjustable shelves (adjustable in <sup>1</sup>/<sub>2</sub>" increments)</li> </ul>
	Forced draft air circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Heavy duty door handles
	<ul> <li>Swivel casters (3 <sup>1</sup>/<sub>2</sub>"); Probe access port (3/8")</li> </ul>
	LED interior lights are safety shielded and switch controlled
	<ul> <li>Powder coated steel white interior and exterior</li> </ul>
	High density urethane foam cabinet insulation
	Hydrocarbon, natural refrigerant (R290)
	<ul> <li>One year parts and labor warranty, plus an additional four year compressor parts warranty</li> </ul>
	• Exterior dimensions: 39 $5\!\!\!/_8$ " W x 34 $3\!\!'_4$ " D x 81 $3\!\!'_4$ " H with casters; 78 $1\!\!'_4$ " H without casters
	Cycle defrost
	• 115V, 60 Hz, 4.5 Amps, 1/4 HP
	ETL listed
	Shipping weight: 405 lbs.