

**SPEC SHEET ABT-HC-SSP-49**

<b>Product Name:</b>	ABT-HC-SSP-49
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Premier Stainless Steel Laboratory Refrigerator</li> <li>• 49 Cu. Ft. Capacity</li> <li>• Two stainless steel swing doors</li> <li>• Microprocessor temperature controller</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Remote alarm contacts</li> <li>• Adjustable operating temperature range: 1°C -10°C</li> <li>• Six adjustable shelves</li> <li>• Forced draft air circulation</li> <li>• Keyed door locks; Magnetic door gasket for positive seal</li> <li>• Integrated door handles</li> <li>• Swivel casters (adds 6 ½" to height)</li> <li>• Interior light</li> <li>• Probe access port (3/8")</li> <li>• Stainless steel interior floor; Stainless steel exterior</li> <li>• High density urethane foam cabinet insulation</li> <li>• Hydrocarbon, natural refrigerant (R290)</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts warranty</li> <li>• Exterior dimensions: 54" W x 35 3/4" D x 83 1/4" H with casters; 77 ½" H without casters</li> <li>• Cycle defrost</li> <li>• 115V, 60 Hz, 4.5 Amps, 1/4 HP</li> <li>• ETL listed</li> <li>• Shipping weight: 450 lbs.</li> </ul>