



## SPEC SHEET ABT-MFP-30

Product Name:	ABT-MFP-30
Features:	Premier Manual Defrost Laboratory Freezer
	• 30 Cu. Ft. capacity
	One solid swing door, right hinged, not reversible
	<ul> <li>Five inner "fast-freeze compartments" with doors for temperature maintenance and recovery</li> </ul>
	Microprocessor Temperature Controller
	<ul> <li>Adjustable operating temperature range: -15°-25°C</li> </ul>
	<ul> <li>Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</li> </ul>
	• Sample simulated digital temperature display; .1° Resolution
	Adjustable temperature display in Celsius or Fahrenheit
	<ul> <li>Audible and visual high/low temperature alarms</li> </ul>
	Sensor error alarm
	Power failure alarm
	Resettable 1-point Min/Max History
	Remote alarm contacts
	<ul> <li>Alarm validation (audible, visual, and remote alarm)</li> </ul>
	Alarm mute with ring back
	Four fixed shelves
	Keyed door lock
	Magnetic door gasket for positive seal
	Stainless steel door handle
	<ul> <li>Caster platform (adds 4" to height)</li> </ul>
	One probe access port (3/8")
	White textured cabinet and door
	High density urethane foam cabinet and door insulation





## SPEC SHEET ABT-MFP-30

<ul> <li>Features:</li> <li>CFC-free refrigerant (R404a), foam insulation and packaging</li> <li>Two year parts and labor warranty; plus additional three year compressor parts warranty</li> <li>Exterior dimensions: 35 <sup>3</sup>/<sub>4</sub> W x 34 <sup>1</sup>/<sub>4</sub> D x 76 <sup>1</sup>/<sub>2</sub> H with</li> </ul>	Product Name:
<ul> <li>Caster platform; 72 ½" H without caster platform</li> <li>Manual defrost</li> <li>115V, 60 Hz, 6 Amps, 1/3 HP</li> <li>UL/C-UL listed</li> <li>Shipping weight: 462 lbs.</li> </ul>	