

SPEC SHEET CRT-ABT-HC-S36G

Product Name:	CRT-ABT-HC-S36G
Features:	<ul style="list-style-type: none"> • Upright Controlled Room Temperature Cabinet, Glass Door • 36 Cu. Ft. Capacity • Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated) • Microprocessor temperature controller • Audible and visual high and low temperature alarms • Remote alarm contacts • Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • 2 probes; 1 in air and 1 in sample bottle • Eight adjustable shelves • Vaccine storage power cord warning label • Forced draft air circulation • Keyed door lock • Magnetic door gasket for positive seal • Heavy duty door handles • Swivel Casters (3”) • LED interior lights are safety shielded and switch controlled • Probe access port (3/8”) • Powder coated steel white interior and exterior • High density urethane foam cabinet insulation • Hydrocarbon, natural refrigerant (R290)

SPEC SHEET CRT-ABT-HC-S36G

<p>Product Name:</p>	<p>CRT-ABT-HC-S36G</p>
<p>Features:</p>	<ul style="list-style-type: none"> • One year parts and labor warranty, plus an additional four year compressor parts warranty • Exterior dimensions: 39 5/8" W x 34 3/4" D x 81 3/4" H with casters; 78 1/4" H without casters • Cycle defrost • 115V, 60 Hz, 4.5 Amps, 1/4 HP • ETL listed • Shipping weight: 405 lbs.