



## SPEC SHEET CRT-ABT-HC-S49G

Product Name:	CRT-ABT-HC-S49G
Features:	<ul><li>Upright Controlled Room Temperature Cabinet, Glass Door</li><li>49 Cu. Ft. Capacity</li></ul>
	<ul> <li>Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated)</li> </ul>
	Microprocessor temperature controller
	Digital temperature display
	<ul> <li>Audible and visual high and low temperature alarms</li> </ul>
	Remote alarm contacts
	<ul> <li>Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</li> </ul>
	<ul> <li>Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable</li> </ul>
	• 2 probes; 1 in air and 1 in sample bottle
	Eight adjustable shelves
	Vaccine storage power cord warning label
	Forced draft air circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Heavy duty door handles
	Swivel Casters (3")
	LED interior lights are safety shielded and switch controlled
	<ul> <li>Probe access port (¾")</li> </ul>
	Powder coated steel white interior and exterior
	High density urethane foam cabinet insulation
	Hydrocarbon, natural refrigerant (R290)





## SPEC SHEET CRT-ABT-HC-S49G

Product Name:	CRT-ABT-HC-S49G
Features:	<ul> <li>One year parts and labor warranty, plus an additional four year compressor parts warranty</li> <li>Exterior dimensions: 54" W x 34 ¾" D x 81 ¾" H with casters; 78 ¼" H without casters</li> <li>Cycle defrost</li> <li>115V, 60 Hz, 4.5 Amps, 1/4 HP</li> <li>ETL listed</li> <li>Shipping weight: 538 lbs.</li> </ul>