

SPEC SHEET PH-ABT-HC-RFC1020G

Product Name:	PH-ABT-HC-RFC1020G
Features:	<ul style="list-style-type: none"> • Premier Pharmacy Refrigerator & Freezer Combination (-20°C) • Freestanding • 5.2 cu. ft. capacity (Refrigerator) / 4 cu. ft. capacity (Freezer) • One glass swing door (fridge), one solid swing door (freezer) • Microprocessor temperature controller • Digital temperature display • Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle • Remote alarm contacts • Adjustable operating temperature range - Freezer: 5°F – -13°F (-15° C – -25°C) Refrigerator: 36°F to 46°F (2°C to 8°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • 2 fixed shelves (freezer); 3 adjustable shelves (fridge) • Bottom footed shelf to allow air circulation • Back wall evaporator cover • Keyed door locks • Magnetic door gasket for positive seal • Recessed door handles • Stacking kit • Leveling legs • LED interior light • Probe access port (3/8") • White cabinet and door

SPEC SHEET PH-ABT-HC-RFC1020G

Product Name:	PH-ABT-HC-RFC1020G
Features:	<ul style="list-style-type: none"> • High density urethane foam cabinet and door insulation • HFC-free refrigerant (R600a), foam insulation and packaging • Two year parts and labor warranty, plus an additional three year compressor parts only warranty • Exterior dimensions: 23 3/4" W x 24" D x 65" H • Note: This unit must have 4" clearance on sides and back for adequate ventilation • Manual defrost (freezer); Cycle defrost (refrigerator) • 115V, 60 Hz • 1.4 Amps, 1/8 HP (freezer); 1.3 Amps, 1/6 HP (refrigerator) • UL/C-UL listed • Shipping weight: 266 lbs.