

**SPEC SHEET PH-ABT-HC-RFC1040G**

<b>Product Name:</b>	PH-ABT-HC-RFC1040G
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Premier Pharmacy Refrigerator &amp; Freezer Combination (-40°C)</li> <li>• Freestanding</li> <li>• 5.2 cu. ft. capacity (Refrigerator) / 4 cu. ft. capacity (Freezer)</li> <li>• One glass swing door (fridge), one solid swing door (freezer)</li> <li>• Microprocessor temperature controller</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Remote alarm contacts</li> <li>• Adjustable operating temperature range- Freezer: -35°F to -45°F (-37°C to 43°C) Refrigerator: 36°F to 46°F (2°C to 8°C)</li> <li>• Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm</li> <li>• 3 adjustable shelves (freezer); 3 adjustable shelves (fridge)</li> <li>• Bottom footed shelf to allow air circulation</li> <li>• Back wall evaporator cover</li> <li>• Keyed door locks</li> <li>• Magnetic door gasket for positive seal</li> <li>• Recessed door handles</li> <li>• Stacking kit</li> <li>• Leveling legs</li> <li>• LED interior light</li> <li>• Probe access port (3/8")</li> <li>• White cabinet and door</li> </ul>

**SPEC SHEET PH-ABT-HC-RFC1040G**

<b>Product Name:</b>	PH-ABT-HC-RFC1040G
<b>Features:</b>	<ul style="list-style-type: none"> <li>• High density urethane foam cabinet and door insulation</li> <li>• HFC-free refrigerant (R600a) Refrigerator; Natural, Hydrocarbon refrigerant (R290) Freezer</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts only warranty</li> <li>• Exterior dimensions: 23 3/4" W x 24" D x 65" H</li> <li>• Note: This unit must have 4" clearance on sides and back for adequate ventilation</li> <li>• Manual defrost (freezer); Cycle defrost (refrigerator)</li> <li>• 115V, 60 Hz</li> <li>• 2.2 Amps, 1/4 HP (freezer); 1.3 Amps, 1/6 HP (refrigerator)</li> <li>• UL/C-UL listed</li> <li>• Shipping weight: 268 lbs.</li> </ul>