

SPEC SHEET PH-ABT-HC-RFC7A-CAD

Product Name:	PH-ABT-HC-RFC7A-CAD
Features:	<ul style="list-style-type: none"> • Premier Pharmacy/Vaccine Refrigerator & Freezer Combination with Controlled Auto Defrost Freezer • 7 Cu. Ft. capacity (5.2 Ref./1.0 Freezer) • Two exterior swing doors (glass door refrigerator/solid door freezer), right hinged, not reversible • Microprocessor temperature controller, refrigerator and freezer • Digital temperature display with sample simulated probe, refrigerator and freezer • Adjustable operating temperature range: Refrigerator: 36°F - 46°F (2°C - 8°C); Freezer: 5°F – -13°F (-15°C – -25°C) • Defrost: Auto defrost cycle every 6 hours: (at Set Point -11°F /-24°C) • Max air temp in empty freezer: 5°F (-15°C) • Max air temp in loaded freezer: 3°F (-16°C) • Max sample temp in empty freezer: 0°F (-18°C) • Max sample temp in loaded freezer: -4°F (-20°C) • Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable • Audible and visual high and low temperature alarms, refrigerator and freezer • Remote alarm contacts, refrigerator and freezer • 5 adjustable shelves total with guard rail on back to prevent product from being pushed against back wall • 3 adjustable shelves, Refrigerator; 2 adjustable shelves, Freezer Bottom footed shelf to allow air circulation, Refrigerator and Freezer • Vaccine storage power cord warning label • Forced draft circulation Refrigerator • Keyed door locks

SPEC SHEET PH-ABT-HC-RFC7A-CAD

Product Name:	PH-ABT-HC-RFC7A-CAD
Features:	<ul style="list-style-type: none"> • Magnetic door gasket for positive seal • Integrated door handles • Leveling legs • Stacking kit • Two probe access ports (3/8"); one, refrigerator/one, freezer • White powder coated exterior • HFC-free refrigerant (R600a), foam insulation and packaging • Pharmacy refrigerator/freezer toolkit and temperature logs • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Pyxis®, Omnicell® and AcuDose RX® compatible • Exterior dimensions: 23 3/4" W x 24 1/4" D x 53 1/8" H • Controlled auto defrost freezer / cycle defrost refrigerator • 115V, 60 Hz, 2.3 Amps refrigerator, 1 Amp freezer, 1/3 HP refrigerator, 1/8 HP freezer • UL/C-UL listed • Shipping weight: 207 lbs. • In stock, with next day shipping • *Please note this unit requires 2 outlets.