

SPEC SHEET PH-ABT-HC-RFC9SS-LH

Product Name:	PH-ABT-HC-RFC9SS-LH
Features:	<ul style="list-style-type: none"> • Premier Pharmacy/Vaccine Refrigerator & Freezer Combination • 9 Cu. Ft. Capacity (4.5 Ref./4.2 Freezer) • Two stainless steel exterior swing doors, left hinged, not reversible • Microprocessor temperature controller, refrigerator and freezer • Digital temperature display, refrigerator and freezer • Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • Audible and visual high and low temperature alarms, refrigerator and freezer • 2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer • Remote alarm contacts, refrigerator and freezer • 2 adjustable/1 fixed shelves refrigerator/2 fixed shelves freezer with guard rails on back in Refrigerator to prevent product from being pushed against back wall • Back wall evaporator cover, Refrigerator • Forced draft circulation, Refrigerator • Vaccine storage power cord warning label • Keyed door locks • Magnetic door gasket for positive seal • Recessed door handles • Leveling legs • Stacking kit

SPEC SHEET PH-ABT-HC-RFC9SS-LH

Product Name:	PH-ABT-HC-RFC9SS-LH
Features:	<ul style="list-style-type: none"> • LED interior lights • Probe access port (3/8"), 2 ea. (1 for refrigerator/1 for freezer) • Stainless steel exterior • HFC-free refrigerant (R600a), foam insulation and packaging • Pharmacy refrigerator/freezer toolkit and temperature logs • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Exterior dimensions: 23 ¾" W x 24 ½" D x 66 ¾" H • Manual defrost freezer / cycle defrost refrigerator • 115V, 60 Hz, 1.74 Amps Refrigerator, 1.5 Amps Freezer, 1/8 HP Refrigerator and Freezer • UL/C-UL listed • Shipping weight: 266 lbs. • *Please note this unit requires 2 outlets.