



## SPEC SHEET PH-ABT-HC-S12G

Product Name:	PH-ABT-HC-S12G
Features:	Standard Pharmacy/Vaccine Glass Door Refrigerator
	• 12 Cu. Ft. Capacity
	<ul> <li>One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible</li> </ul>
	Microprocessor temperature controller
	Digital temperature display
	<ul> <li>Audible and visual high and low temperature alarms</li> </ul>
	Remote alarm contacts
	<ul> <li>2 probes; 1 in air and 1 in sample bottle</li> </ul>
	<ul> <li>Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)</li> </ul>
	<ul> <li>Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm</li> </ul>
	<ul> <li>Three adjustable shelves (adjustable in ½" increments)</li> </ul>
	Vaccine storage power cord warning label
	Forced draft air circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Heavy duty door handle
	• Swivel Casters (3 <sup>1</sup> / <sub>2</sub> ")
	LED interior lights are safety shielded and switch controlled
	<ul> <li>Probe access port (<sup>3</sup>/<sub>8</sub>")</li> </ul>
	<ul> <li>Powder coated steel white interior and exterior</li> </ul>
	High density urethane foam cabinet insulation
	Hydrocarbon, natural refrigerant (R290)





## SPEC SHEET PH-ABT-HC-S12G

Product Name:	PH-ABT-HC-S12G
Features:	<ul> <li>Pharmacy refrigerator/freezer toolkit and temperature logs</li> <li>One year parts and labor warranty, plus an additional four year compressor parts warranty</li> <li>Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters</li> <li>Cycle defrost</li> <li>115V, 60 Hz, 3 Amps, 1/5 HP</li> <li>ETL listed</li> <li>Shipping weight: 258 lbs.</li> </ul>