

ThermalSeal® RTS™

Effective: June 27, 2014
Document No.: MFG-PS-404 RevE

Dimensional Information and Tolerances

CRITERIA	DIMENSIONAL INFORMATION / SPECIFICATIONS
Sheeted Film:	
Overall (L x W)	5.500" +/- 0.015 x 3.0833" +/- 0.015
End-Tabs	0.375" +/- 0.015
Perforations	0.4625" +/- 0.015 from edge of film
Corner Radii	N/A
Roll Stock:	
Roll W x L	79mm x 65 meters (3.093" x 214')
Slit Width Tolerance	1/32"

Construction

LAYER	DESCRIPTION	THICKNESS
Top Coat	N/A	N/A
Film	Optically Clear Polyolefin	2.0 mil +/-10%
Adhesive *	Pressure-Sensitive Silicone	1.8 - 2.2 mil
Release Liner	White Polyester	2.0 mil +/-10%

* Note: Gamma radiation will slightly reduce the tackiness of the adhesive

Applications

- Real-Time qPCR
- Protein Crystallization
- Storage

Features & Benefits

- High optical clarity, low auto-fluorescence
- Certified free of detectable levels of DNase-, RNase- and Human/Mouse DNA
- Chemically inert; no extractables except at extreme pH
- Excellent chemical resistance (e.g. DMSO, Methanol, Acetonitrile)
- Heat and cold resistant, recommended for temperatures from -80°C to 105°C
- Fits within raised plate rim to prevent loss of seal due to film lifting

