

MidSci™

Z366 Series

Z366
Z366-K

Universal Centrifuges



- **Mid-Range capacity**, 4 x 250ml rotor (16x50ml or 40x15ml)
- Advanced programming with auto rotor recognition
- High speed rotors available providing up to 24,000 x g
- Available with refrigeration



Z366 Universal Centrifuge



Refrigerated

Z366-K Universal Centrifuge

Z366 Series Summary

Speed up to 16,000 rpm

G-Force up to 24,325 x g

Swing Out Capacity:

4 x 250 ml

12 x 50 ml

28 x 15ml

6 x microplates

Angle Rotor Capacity

44 x 1.5/2.0 ml

30 x 15 ml

10 x 50 ml

6 x 250 ml

Z366 Features

Microprocessor Control

Over-speed protection

Automatic rotor identification

Program Storage (99)

Pre-Cool function (Z366-K only)

Momentary spin button

Imbalance detection

Adjustable Accel/Decel

Audible end of run alarm

Maintenance free induction drive

Motor driven safety lid-lock

Quiet operation, less than 62 DB

Splash proof display

Powerful Refrigeration (Z366-K only)

Z366 Specifications

Speed Range: 200 to 16,000 rpm*

Max. RCF: 24,325 x g*

Max Capacity: 4 x 250 ml (Swing out)

6 x 250 ml (Angle)

Timer: up to 99 hr, 59 min.

Dimensions: 17 x 20 x 14.2 in.

(W x D x H) 43 x 51 x 36 cm.

Z366-K 28.3 x 20 x 14.2 in.

72 x 51 x 36 cm.

Weight: 114 lbs (52 kg)

Z366-K 169 lbs (77 kg)

Electrical: 120 or 230V, 50/60Hz

Power Draw: 520W (Z366-K: 785W)

Temp Range: -20° - 40° C

(Z366-K only)

*Max Speed of Z366: 15,000rpm/21,379xg



For applications requiring increased capacity over the Z306 or Z326 series centrifuges, the Z366 series offer a unique “Mid-Range” swing out rotor that accepts a variety of different tubes, including up to 16 x 50ml or 40 x 15ml.

Despite this step up in capacity, the Z366 maintains a surprisingly compact design, with the standard air-cooled model featuring a footprint of 17 x 20 inches.

In addition to the popular 4 x 250ml swing out rotor, a variety of additional rotors are also available. Angled rotors range from a 24 x 1.5ml micro rotor to a high capacity 6 x 250ml rotor. A 2 x 3 position microplate rotor is also available, as well as a 4 x PCR strips (8-strips).

Advanced microprocessor controls allow for instant rotor identification, which automatically converts the rotational speed to the relevant g-force (rcf), preventing the user from setting a speed above the capabilities of the installed rotor. In addition to retrieving saved programs, the easy to use front panel can adjust accel/decel rates, and change the end of run alarm tone.

Ordering Information:

Z366* Z366 Centrifuge (without rotor), 120V

Z366-K* Z366-K Refrigerated Centrifuge (without rotor), 120V

*115V with US Plug. For 230V (EU Plug), please order -E.

Universal Swing Out Rotor:



Item: Z366-250

4 x 250ml Swing Out Rotor

Max Speed: 4,500 rpm / 3,780 x g

Accel: 34 sec. / Decel: 36 sec.

Inserts:	Tube	qty/ insert	qty./ rotor
Z366-250-A250	250ml	1	4
Z366-250-A100	100ml	1	4
Z366-250-A50	50ml conical	3	12
Z366-250-A15	15ml conical	7	28
Z366-250-A10	10ml	8	32
Z366-250-A57	5/7ml	14	56
Z366-250-LID	Hermetically Sealed Lid, 2/pk	1	4



Z366-250-LID



Item: Z366-250-HC

4-place High Capacity Swing Out Rotor

Max Speed: 4,500 rpm / 3,735 x g

Accel: 34 sec. / Decel: 36 sec.

Inserts:	Tube	qty/ insert	qty./ rotor
Z366-250-B50	50ml conical	4	16
Z366-250-B15	15ml conical	10	40
Z366-250-B10	10ml	12	48
Z366-250-B57	5/7ml	14	56

*Inserts sold in 2/pk.
Rotor accepts 4 inserts (2 x 2/pk.)

Additional Rotors:



Item: Z366-06250

6 x 250ml Angle Rotor (28°)

Max Speed: 8,000 rpm / 10,016 x g

Accel: 130 sec. / Decel: 92 sec.



Item: Z326-0685

6 x 85ml Angle Rotor (38°)

Max Speed: 11,000 rpm / 15,555 x g

(Z366)

Max Speed: 13,000 rpm / 21,726 x g

(Z366K)

Accel: 85 sec. / Decel: 70 sec.*



Item: Z326-0650-HS

6 x 50ml Angle Rotor (26°) Round

Max Speed: 13,000 rpm / 15,869 x g

Accel: 48 sec. / Decel: 49 sec.



Item: Z326-1050

10 x 50ml Angle Rotor (38°) Conical

Max Speed: 9,000 rpm / 11,771 x g

(Z366)

Max Speed: 10,500 rpm / 16,022 x g

(Z366-K)

Accel: 22 sec. / Decel: 23 sec.*

Inserts/Adapters

Z366-06250-A15: 3 x 15ml conical

Z366-06250-A50R: 50ml round

Z366-06250-A50: 50ml conical

Inserts/Adapters

Z326-85-A15R: 15ml round

Z326-85-A15: 15ml conical

Z326-85-A50R: 50ml round

Z326-85-A50: 50ml conical

Inserts/Adapters

Z326-50-A30: 30ml round

Z326-50-A15R: 15ml (conical or round)

Inserts/Adapters

Z326-50-A30: 30ml round

Z326-50-A15: 15ml conical

Z326-50-B15: 15ml round

Z206-50-A57: 5-7ml (12-13mm)

Z206-50-A57C: Cushion for 5ml tube

*Acceleration and deceleration provided for the maximum speed of model Z366.

Additional Rotors (Continued):



Item: Z326-2010

20 x 10ml Angle Rotor (30°)
Max Speed: 12,000 rpm / 15,775 x g
Accel: 54 sec. / Decel: 47 sec.



Item: Z326-2420

24 x 1.5/2.0ml Angle Rotor with Quick-Seal lid (40°)
Max Speed: 15,000 rpm / 21,379 x g (Z366)
Max Speed: 16,000 rpm / 24,325 x g (Z366K)
Accel: 25 sec. / Decel: 26 sec.*



Item: Z326-2420H

24 x 1.5/2.0ml Angle Rotor (40°) Hermetically Sealed Lid
Max Speed: 15,000 rpm / 21,379 x g (Z366)
Max Speed: 16,000 rpm / 24,325 x g (Z366K)
Accel: 25 sec. / Decel: 26 sec.*



Item: Z326-4420

44 x 1.5/2.0ml Angle Rotor with Quick-Seal lid (32°/55°)
Max Speed: 15,000 rpm / 21,379 x g (Z366)
Max Speed: 16,000 rpm / 24,325 x g (Z366)
Accel: 29 sec. / Decel: 28 sec



Item: Z326-3015

30 x 15ml Angle Rotor (35°)
Max Speed: 4500 rpm / 2830 x g
Accel: 25 sec. / Decel: 20 sec.



Item: Z326-02MP

Swing Out Rotor 2 x 3 microplates (90°)
Max Speed: 4500 rpm / 2716 x g
Accel: 43 sec. / Decel: 38 sec.

Inserts/Adapters

C3100-ADP: 5-7ml (12-13mm)

Inserts

BT1500-A1520: 20 x 1.5ml
BT1500-A05: 20 x 0.5ml
Z326-MPCA: 3 x chamber slide and dish carrier
2/pk

New optional accessory!!! Z326-MPCA

Universal 3 x chamber slide and dish carrier



Chamber Slides



35mm Dishes



60mm Dishes

Fits all Hermle microplate carriers!!!

MIDSCI™

www.midsci.com

PH: 800-227-9997 EM: leads@midsci.com

*Acceleration and deceleration provided for the maximum speed of model Z366.

Also Available:

Z446 Series High Capacity Centrifuges

Swing Out Rotor Accepts up to:

- 68 x 15ml conical tubes
- 28 x 50ml conical tubes
- 16 x microplates

